


TPIN	SYMBOL	TPIN	SYMBOL
1	A	26	Q1
2	A	27	Q2
3	R	28	R7
4	R	29	R8
5	GND	30	R9
6	VCOM/0.9V	31	R1
7	D10	32	R3
8	R06	33	R5
9	PE9	34	R1
10	VS0	35	R0
11	R50	36	Q0
12	R1	37	BC1A
13	R6	38	Q0
14	R5	39	SHR
15	B4	40	D0V1
16	R3	41	V0V1
17	R2	42	UGL(PV)
18	R1	43	R0V0(0.9V)
19	R0	44	R5TB
20	Q7	45	NC
21	Q9	46	VCOM
22	Q5	47	BT1H
23	B4	48	Q3
24	Q2	49	NC
25	Q2	50	NC



1	Operating Voltage:	VCC=3.3V typ.
2	Resolution:	800RGB*480
3	Color:	16M
4	Interface:	24 BIT RGB
5	Display type:	Transmissive TN
6	Viewing Direction:	12:00
7	Operating Temp:	-30°C~80°C
8	Storage Temp:	-30°C~85°C
9	Driver IC:	HX8264-E, HX8664-B
10	CTP Driver IC:	
11	LCM Luminance:	845(MIN), 1100(TYP)cd/m2
12	Unspecified tolerance:	±0.3