



8.4V(min.)-9.8V(typ.)-11V(max.)@If=180mA

FPC	PIN	SYMBOL	PIN	SYMBOL
	1	VCOM(-0.70V)	21	RXIN3+
	2	VDD	22	GND
	3	VDD	23	NC
	4	NC	24	NC
	5	RESET	25	GND
	6	STBYB	26	NC
	7	GND	27	DIM0
	8	RXIN0-	28	SELB
	9	RXIN0+	29	AVDD(+1.1V)
	10	GND	30	GND
	11	RXIN1-	31	LED-
	12	RXIN1+	32	LED-
	13	GND	33	L/R
	14	RXIN2-	34	U/D
	15	RXIN2+	35	VEL(-TV)
	16	GND	36	CABCEN1
	17	RXCLKIN-	37	CABCEN0
	18	RXCLKIN+	38	VBE(-20V)
	19	GND	39	LED+
	20	RXIN3-	40	LED+

1	Operating Voltage:	VDD=3.3V typ.
2	Resolution:	1024RGB*600
3	Color:	16.2M
4	Interface:	LVDS
5	Display type:	Transmissive, TN, Normally White
6	Viewing Direction:	12:00
7	Operating Temp:	-20°C~60°C
8	Storage Temp:	-30°C~70°C
9	Driver IC:	NT51008*1&NT52002*2
10	LCM Luminance:	230cd/m ² (Typ)
11	Unspecified tolerance:	±0.3